ACOUSTIC FELT SILENTIUM® 25/3000

Acoustic felt SILENTIUM® is an excellent sound absorber of absorber class A. The material is 100% manufactured in Germany. It is made of OEKO-TEX® Standard 100 polyester class 1 (suitable for baby articles) and partly recycled polyester, up to 30% depending on the colour. Due to its high inherent stability, it does not need a frame.

Acoustic felt Made in Austria

Material Made in Germany

Zertifizierungen Oeko-Tex® Standard 100, class 1 for baby articles **Mounting** Invisible fastening with magnets | invisible nailing

Material strength 25mm
Weight 3.000 g/m²

Size 700 x 500mm | 500 x 500mm

Fire rating Flame retardant according to DIN 4102 (B1)


Versions 7050 | 5050

Colours White | Light grey | Grey | Anthracite | Black

Sound absorption coefficient

DIN EN ISO 354

50 mm



Structure	Rating according to ISO 11654	Rating according to ASTN

without distance Sound absorption coefficient: $\alpha_W = 0,60$ Noise Reduction Coefficient NRC = 0.80

Sound absorption class: C Sound Absorption Average SAA = 0.78 Sound absorption coefficient: $\alpha_W = 0.90$ Noise Reduction Coefficient NRC = 0.85

Sound absorption class: A Sound Absorption Average SAA = 0.88

200 mm Sound absorption coefficient: αw = 1.00 Noise Reduction Coefficient NRC = 1.00

Sound absorption class: A Sound Absorption Average SAA = 1.01



Care instructions / irregularities with SILENTIUM®

Cleaning: Vacuum carefully. Avoid rubbing and scouring the surface. The following irregularities of SILENTIUM® are possible despite sophisticated processing technology and do not reduce the value or function of the panels in any way: Occasionally, individual darker fibres may be visible, which are part of the characteristics of SILENTIUM®. Due to the nature of the material, minimal thickness differences in the thickness of the panels cannot always be avoided.